

Table of specifications

MC type Magnetic Contactors



Frame size		18AF				22AF			
Type	screws clamp terminals	MC-6a	MC-9a	MC-12a	MC-18a	MC-9b	MC-12b	MC-18b	MC-22b*
Number of poles				3pole				3pole	
Rated operational voltage, Ue				690V				690V	
Rated insulation voltage, Ui				690V				690V	
Rated frequency				50/60Hz				50/60Hz	
Rated impulse withstand voltage, Uimp				6kV				6kV	
Maximum operating rate in operating cycles per hour(AC3)		1800 operations per hour				1800 operations per hour			
Durability	Mechanical	15 mil. operations				15 mil. operations			
	Electrical	2.5 mil. operations				2.5 mil. operations			
Current and power	AC-1, Thermal current AC-3 200/240V A	25	25	25	32	25	25	32	40
	380/440V kW	2.2	2.5	3.5	4.5	2.5	3.5	4.5	5.5
	A	9	11	13	18	11	13	18	22
	500/550V kW	3	4	5.5	7.5	4	5.5	7.5	11
	A	7	9	12	18	9	12	18	22
	690V kW	3	4	7.5	7.5	4	7.5	7.5	15
	A	6	7	12	13	7	12	13	20
		3	4	7.5	7.5	4	7.5	7.5	15
		4	5	9	9	6	9	9	18
UL rating (50/60Hz)	Continuous current Single phase	25	25	25	32	25	25	40	40
	110~120V HP	0.5	0.5	0.75	1	0.5	0.75	1	2
	220~240V HP	1.5	1.5	2	3	1.5	2	3	3
	200~208V HP	2	2	3	5	2	3	5	7.5
	Three phase	3	3	5	7.5	3	5	7.5	10
	220~240V HP	5	5	7.5	10	5	7.5	10	15
	440~480V HP	7.5	7.5	10	15	7.5	10	15	20
	550~600V HP	00	00	0	0	00	00	0	1
Size and weight	AC control	Weight kg				0.33			
	DC control	Size(W×H×D) mm				45×73.5×82			
		Weight kg				0.5			
		Size(W×H×D) mm				45×83×113.7			
Auxiliary(standard)		1a or 1b				1a1b			
Auxiliary	Side mount	UA-1				UA-1			
	Front mount	AU-2, AU-4				AU-2, AU-4			

Note) Minimum conduct current of Auxiliary contactor is DC 17V 5mA.

MT type Thermal Overload Relays



Type	Screws clamp terminals	MT-12□	MT-32□
Rated operational voltage, Ue		690V	690V
Rated insulation voltage, Ui		690V	690V
Rated impulse withstand voltage, Uimp		6kV	6kV
Trip class		10A, 20	10A, 20
Setting range		0.1~18A	0.1~40A
Size and weight	Weight kg	0.1	0.17
	Size(W×H×D) mm	45×73.2×63.7	45×75×90

* The safety cover of magnetic contactor and thermal overload relay is optional.